



Aroma SE 200/300

Description

Arome SE 200 and SE 300 are both equipped with electronic pre-brewing and electronic adjustable servings.

Created to satisfy every professional requirement, the Aroma line is an embodiment of the high-quality technology Saeco is famous for.

Main features

- Autonomously pre-heated brewing group with adjustable temperature maintains the perfect temperature for any sort of coffee beans independent of how long the machine has not been used
- Double pre-brewing system: mechanical only, or mechanical and electronic
- Top boiler capacity one of the highest available
- Main switch with 3 positions full power, reduced power and energy saving mode for electric heating
- Teflon-coated volumetric meter and cold nozzle with T.E.A. treatment to prevent lime scale

Accessories

- Automatic cappuccinatore
- Digital display
- Water softener







Technical data Aroma SE	.00 Aroma SE 300
-------------------------	-------------------------

Technical data	Al Ollia SE 200	Al Ollia 3L 300
Structural specifications		
Dimensions ($w \times h \times d$)	770 × 540 × 560 mm	980 × 540 × 560 mm
Weight	62.5 kg	77 kg
Framework material	tropicalized steel	tropicalized steel
Housing material	ABS/stainless steel/painted steel	ABS/stainless steel/painted steel
Electrical specifications		·
Power supply	230-240 V/50-60 Hz 400-415 V/50-60 Hz 3N~	230-240 V/50-60 Hz 400-4 5 V/50-60 Hz 3N~
Electric heating at maximum power	5000 - 4500 W	6000 - 5600 W
Electric heating at reduced power	3500 - 3000 W	4200 - 3800 W
Pre-warming cup surface (240V~)	180 W	240 W
Water specifications		
Boiler capacity	131	211
Boiler material	copper	copper
Independent heat exchangers tied to boiler	•	•
Autonomously heated chrome-brass units	2	3
Stainless steel articulated steam wand	2	2
Stainless steel hot water wand	•	•
Pressure gauge for boiler and pump	•	•
Water boiler level indicator	•	•
Boiler filled automatically or manually	•	•
Internal balanced motor pump	•	•
Anti-eddy device in boiler	•	•
Water connections		
Water supply	water supply	water supply
Water connection	3/8" (I-8 bar)	3/8" (1-8 bar)
Other specifications		
Water pre-mixing	•	•
Electronic pre-brewing	•	•
Electronically adjustable servings	•	•
Pods kit	•	•
Number of selections	H	16
Performances		
Steam production/hour	6.9 kg	9.15 kg
Hot water production/hour (150 cc cup)	300	350
Coffee preparations/hour (30 cc cup in 25-30")	300	450

CE and CSA (Aroma SE 200) approved

